

Doncaster Cables

552 SPEAKER CABLE

24/0.2mm COPPER / FIGURE 8 PVC INSULATED





Sales Office: Millfields Industrial Estate, Arksey Lane, Bentley, Doncaster, South Yorkshire DN5 0SJ

Tel: 0844 324 8588

Fax: 0844 324 8584

Email: sales@doncastercables.com



Doncaster Cables

552 SPEAKER CABLE

24/0.2mm COPPER / FIGURE 8 PVC INSULATED


24 strands of 0.2mm oxygen free copper. The conductors are constructed in a flat 'figure of 8' configuration. The insulation is black/red in colour.

Designed for use in connecting loudspeakers to audio appliances and amplifiers.




The general rule of speaker cable is the more strands that the cable has, the better the sound quality. Including higher definition, a richer bass and more musical highs

Conductor : Plain Annealed Copper Class 5 Flexible to BS EN 60228

Insulation: PVC Type T12 to BS EN 50363-3



Reference Number	Nominal Cross Sectional Area of Conductor (mm ²)	Nominal Stranding of Conductor (mm)	Nominal Radial Thickness of insulation (mm)	Approx. Height (Minor Axis) (mm)	Approx. Width (Major Axis) (mm)	Approx. Web Details (mm)	Approx. Weight (kg/km)
552	0.75	24/0.2	0.5	2.2	4.5	0.4x0.2	24

MINIMUM OPERATING TEMPERATURE 	MAXIMUM OPERATING TEMPERATURE 	MINIMUM BENDING RADIUS 
---	---	--