




Doncaster Cables

318-Y (H05VV-F) **Ordinary Duty PVC Insulated and Sheathed Flexible Cords**



Sales Office: Millfield Industrial Estate, Arksey Lane, Bentley, Doncaster, South Yorkshire, DN5 0SJ
Tel: 01302 821700 Fax: 01302 821701 Email: sales@doncastercables.com



Doncaster Cables

318-Y (H05VV-F)

Ordinary Duty PVC Insulated and Sheathed Flexible Cords

Manufactured to BS EN 50525-2-11:2011 Clause 4.2, Table B.2.

Annealed Flexible Copper Conductor / PVC Insulated / PVC Sheathed. 300/500V

Conductor : Plain Annealed Copper Class 5 Flexible to BS EN 60228

Insulation: PVC Type TI2 to BS EN 50363-3

Sheathing: PVC Type TM2 to B EN 50363-4-1

Current Ratings: For current ratings refer to table 4F3 of BS7671 IEE Wiring Regulations Seventeenth Edition.

Ordinary duty flexible cords are used where the risk of mechanical damage and mechanical stresses is normal, i.e. when cables are subject to low mechanical stresses in the areas of application, and the risk of mechanical damage is low, as is the case to be expected in the normal use of small to medium size equipment in domestic and commercial as well as in light industrial premises.

Examples of appliances that use ordinary duty flexible cords include vacuum cleaners, toasters, washing machines, refrigerators, dryers and televisions.

STANDARD CORE COLOURS	MINIMUM OPERATING TEMPERATURE	MAXIMUM OPERATING TEMPERATURE	MINIMUM BENDING RADIUS
2 CORE 3 CORE 4 CORE 5 CORE			

DONCASTER CABLES



Doncaster Cables

318-Y (H05VV-F)

Ordinary Duty PVC Insulated and Sheathed Flexible Cords

Reference Number	Harmonisation Code	Nominal Cross Sectional Area of Conductor (mm ²)	Nominal Stranding of Conductor (mm)	Nominal Radial Thickness of insulation (mm)	Nominal Radial Thickness of sheath (mm)	Overall Diameter Lower Limit (mm)	Overall Diameter Upper Limit (mm)	Approximate Weight (kg/km)
3182Y0.75	H05VV-F	0.75	24/0.2	0.6	0.8	5.7	7.2	56
3182Y1.0	H05VV-F	1.0	32/0.2	0.6	0.8	5.9	7.5	73
3182Y1.5	H05VV-F	1.5	30/0.25	0.7	0.8	6.8	8.6	95
3182Y2.5	H05VV-F	2.5	50/0.25	0.8	1.0	8.4	10.6	150
3182Y4.0	H05VV-F	4.0	56/0.30	0.8	1.1	9.7	12.1	195
3183Y0.75	H05VV-F	0.75	24/0.2	0.6	0.8	6.0	7.6	69
3183Y1.0	H05VV-F	1.0	32/0.2	0.6	0.8	6.3	8.0	77
3183Y1.25	N/A*	1.25	40/0.2	0.7	0.9	6.9	8.7	90
3183Y1.5	H05VV-F	1.5	30/0.25	0.7	0.9	7.4	9.4	100
3183Y2.5	H05VV-F	2.5	50/0.25	0.8	1.1	9.2	11.4	150
3183Y4.0	H05VV-F	4.0	56/0.30	0.8	1.2	10.5	13.1	252
3184Y0.75	H05VV-F	0.75	24/0.2	0.6	0.8	6.6	8.3	78
3184Y1.0	H05VV-F	1.0	32/0.2	0.6	0.9	7.1	9.0	110
3184Y1.5	H05VV-F	1.5	30/0.25	0.7	1.0	8.4	10.5	150
3184Y2.5	H05VV-F	2.5	50/0.25	0.8	1.1	10.1	12.5	220
3184Y4.0	H05VV-F	4.0	56/0.30	0.8	1.2	11.5	14.3	310
H3185Y0.75	H05VV-F	0.75	24/0.2	0.6	0.9	7.4	9.3	94
H3185Y1.0	H05VV-F	1.0	32/0.2	0.6	0.9	7.8	9.8	132
H3185Y1.5	H05VV-F	1.5	30/0.25	0.7	1.1	9.3	11.6	180
H3185Y2.5	H05VV-F	2.5	50/0.25	0.8	1.2	11.2	13.9	264
H3185Y4.0	H05VV-F	4.0	56/0.30	0.8	1.4	13.0	16.1	370

* NOT HARMONISED . Weight and dimensional information is provided as an approximate guide only.

Product Certification Schedule

Schedule No. 040/001/312
Test Report No. G1TTA037
Prev. Schedule No. 040/001/264
Licensee: DONCASTER CABLES, ARKSEY LANE, BENTLEY, DONCASTER, DN5 0SJ
Factory: DONCASTER CABLES, ARKSEY LANE, BENTLEY, DONCASTER, DN5 0SJ
Specification BS EN 50525-2-11:2011 - Electric cables - Low voltage energy cables of rated voltages up to and including 450/750 V (Uo/U) Part 2-11: Cables for general applications - Flexible cables with thermoplastic PVC insulation
Type of Cable Clause 4.2 Ordinary duty cables - H05VV-F and H05VVH2-F
Table B.2 Cables rated at 300/500 V
HAR Document EN 50525-2-11:2011
HAR Specification Circular cables: H05VV-F; Flat cables: H05VVH2-F
Range of Approval 0.75sqmm to 4sqmm nominal cross-sectional area of conductors inclusive. 2-core to 5-core inclusive. Class 5 conductor. Circular cables. 0.75sqmm to 1.5sqmm nominal cross-sectional area of conductors inclusive. 2-core. Class 5 conductor. Flat cables. Sheath - TM2. Insulation - TI2.
Origin Thread BLUE/BROWN/GREY/ORANGE
Origin Mark DONCASTER CABLES or GB CABLES or LYON CABLES

PERMISSIBLE MARKS



BASEC ◁ HAR ▷

BLACK - 1cm
RED - 1cm
YELLOW - 3cm
THREAD


Note: The black - red - yellow thread has been registered in this country as an identification thread in the BSI "Register of colours of manufacturers' threads for electric cables and cords" for Verband Deutscher Elektrotechniker (VDE) e.V., Frankfurt, Germany. VDE has authorized BASEC to use this thread.

Please refer the BASEC Product Certification Requirements

Expiry Date: 05/02/2017

This certificate is issued according to the rules of the HAR agreement, wherein the certificate issued by any certification body adhering to the HAR agreement has the same worth and validity in all the other certification bodies' countries. This licence demonstrates the conformity with the essential requirements of the Directive 2006/95/EC (LVD)

Signed for and on behalf of the British Approvals Service for Cables



Date 05/02/2014



This Certificate and Schedule(s) remains the property of BASEC, and shall be returned when required.

004

BSF060.002/A1037