



# LED Panels

- Energy savings up to 60% when replacing 4 x 18W T8 luminaires
- Luminaire efficacy up to 100 Lumen/Watt
- Suitable for 25mm and 15mm T-bar ceilings
- 30W LED, 3000 Lumen
- IP20 rated
- Flicker-free
- Standard non dimmable driver included
- L1A and L2B Building Regulations Compliant
- Colour temperature: 3000K, 4000K and 6000K options
- Colour rendering index: >80
- Rated Life (L70): 50,000 hours
- Options available:
  - 600 x 600mm surface mounting frame
  - Dimmable driver 1-10V and DALI
  - Dimmable driver Touch (Push) and DALI
  - Emergency 3 hour maintained remote pack

## Technical Specifications

**5 YEAR**  
WARRANTY

Part No.	Description	Dimensions (W x H x D mm)	Colour Temperature
<b>LED Panels</b>			
<b>DCLEDPAN3066WW</b>	LED Panel, Warm White	595 x 595 x 10.5	3000K
<b>DCLEDPAN3066NW</b>	LED Panel, Neutral White	595 x 595 x 10.5	4000K
<b>DCLEDPAN3066CW</b>	LED Panel, Cool White	595 x 595 x 10.5	6000K
<b>Accessories</b>			
<b>DCLEDPAN66SMB</b>	Surface Mount Box for LED Recessed Panel		
<b>DCLEDPAN30DND</b>	LED Driver - non dimmable		
<b>DCLLPANDIM-1/10-DALI</b>	45W Dimming LED Driver - dimmable driver (1-10V) and DALI		
<b>DCLLPANDIM-TD</b>	50W Dimming LED Driver - dimmable driver Touch (Push) and DALI		
<b>DCLLPANEM3PACK</b>	Maintained LED Emergency Driver (3hr) Battery Pack		



Doncaster **Cables** | Lighting | Switchgear | Heating

t: 01302 821700

f: 01302 821701

e: sales@doncastercables.com

doncastercables.com